



Elbow



Cross



Tee

公称管子规格		90度弯头 三通 四通 中心到端面 Center to end 90deg Elbow Tee Cross A			45度弯头 中心到端面 Center to end 45deg Elbow C			箍围外径 Outside dia of Band H			最小厚度 Min. Wall Thickness G			螺纹长度 Min Length of thread (note1)	
DN	Nom Pipe Size	2000LBS	3000LBS	6000LBS	2000LBS	3000LBS	6000LBS	2000LBS	3000LBS	6000LBS	2000LBS	3000LBS	6000LBS	B	L2
		6	1/8"	21	21	25	17	17	19	22	22	25	3.18	3.18	6.35
8	1/4"	21	25	28	17	19	22	22	25	33	3.18	3.30	6.60	8.1	10.2
10	3/8"	25	28	33	19	22	25	25	33	38	3.18	3.51	6.98	9.1	10.4
15	1/2"	28	33	38	22	25	28	33	38	46	3.18	4.09	8.15	10.9	13.6
20	3/4"	33	38	44	25	28	33	38	46	56	3.18	4.32	8.53	12.7	13.9
25	1"	38	44	51	28	33	35	46	56	62	3.68	4.98	9.93	14.7	17.3
32	1-1/4"	44	51	60	33	35	43	56	62	75	3.89	5.28	10.59	17.0	18.0
40	1-1/2"	51	60	64	35	43	44	62	75	84	4.01	5.56	11.07	17.8	18.4
50	2"	60	64	83	43	44	52	75	84	102	4.27	7.14	12.09	19.0	19.2

Dimensions in millimeters

Note

1. Dimension B is minimum length of perfect thread. The length of useful thread(B plus threads with fully formed roots and flat crests) shall not be less than L2(effective length of external thread) required by American National Standard for Pipe threads (ASME B1.20.1) See para 6.3